

# TK Tools Industrial equipment

## VL-TYPE MANUAL LEVER BLOCK MODEL: VL-0.25T (61500A), 0.75T (615001A), 1.5T (615002A), 3T (615003A), 6T (615004A)



### Structure

- good quality for the frame, head and chain shall be constructed of aluminium alloy A356-T high strength and rated for 0.25-10 Ton.
- To withstand a working load of 250-10 kg , with a safety factor of 4 with respect to the breaking load.
- With a safety hook to prevent loosening of the power block and that has adequate insurance.
- It shall have a built-in aluminium frame rotating connector that allows you to rotate 360 degrees.

Model	Capacity (t)	Standard lift(m)	Running test load(t)	No.of falls of load chain	Load chain diameter (mm)	Dimension (mm) A	B	C	Net weight (kg)
V 0.5T	0.5	1.5	0.75	1	5	102	80	95	3.5
VL 0.75T	0.75	1.5	1.125	1	6.3	155	88	135	6.6
VL 1.5T	1.5	1.5	2.25	1	7.1	170	110	162	11
VL 3.0T	3	1.5	4.5	1	9	198	120	211	17
VL 6.0T	6	1.5	9	2	9	198	120	254	27.5
VL 9.0T	9	1.5	13.5	3	9	198	120	319	47

